IT R&D Global Leader





# Center Channel Separation based on Spatial Analysis

Dae-young Jang\*, Jung-pyo Hong\*\*, Hoe-Kyung Jung\*\*\* and Kyeongok Kang\* \*ETRI, \*\*ICU, \*\*\*PCU

dyjang@etri.re.kr, rookie@icu.ac.kr, hkjung@pcu.ac.kr, kokang@etri.re.kr


### **Music 2.0 : Interactive Music Service**

• Multi-track interactive music service

Each separated instrument can be selected and controlled

### **Spatial Audio Analysis**

- Multi-track music production using power panning
  - Each track sound is rendered




User mixing, Multiple mixing version, Vocal training
Commercialized in Korea('07 1Q), as a digital music album




#### • Conventional stereo music contents can be break down?

- If yes, you can play with any music contents interactively
- Sound source separation based on spatial analysis is helpful
  - Reversible change maybe possible




- by power panning
- Properly divided T/F slice can be a part of sound source
- If this slice is composed with parts of several sound sources
   *correlation provides a cue*



#### Spatial cues for spatial image for a sound source


- ICLD: Sound source position cue
- ICC: Sound source wideness or portion cue



## **Spatial Filter for Studio Music Signal**

### Sound source position estimation

Single sound image can be exactly estimatedMixed sound image blurred according to ICC value



### Spatial filter using ICLD and ICC parameter


Level

Spatial filter can be devised using ICLD and ICC
Spatial filter for center channel can be implemented by tuning

# **Results and Applications**

### Channel extension

- Surround channel signal can be generated from separated front channel signal
  - Matrix, Reverberator





- Separation degree enhancement
- Applications
  - Channel extension Spatial image control
  - Source separation Parametric Equalization



DAFx-08 September 1-4, 2008 Espoo, Finland